



Waterstop Primer

Water-Based Adhesive Surface Primer for use with Type 10, 15, 20, 20T, 23, and 125CR Strip Applied Waterstops

Earth Shield® Water-Based Adhesive Surface Primer is designed to adhere Earth Shield Strip Applied Waterstops (Type 10, 15, 20, 20T, 23, and 125CR) to concrete, plastic, metal, and wood substrates.

Water-Based Adhesive Surface Primer Typical Physical Properties	
Color	Bright Orange
% Solids	33% minimum
Solvent Type	Water
Flash Point	200°F
Weight per Gallon	8 lbs.
Dry Time at 77°F (25°C)	10 minutes
Dry Time at 40°F (4°C)	60 minutes
Clean-up Wet	Soap and Water
Clean-up Dry	Mineral Spirits

Water-Based Adhesive Surface Primer Typical Physical Properties	
Coverage per gallon	3,000 lft
Acceptable Substrates	Concrete, Plastic, Wood, and Metal
Minimum Storage Temperature	40°F (4°C) Product should not be allowed to freeze
Minimum Application Temperature	40°F (4°C)
Surface When Dry	Tacky

Application Instructions

1. Ensure substrate is clean and free from dirt and debris.
2. If applying to concrete, ensure concrete is dry.
3. Using a small paint brush or roller, apply a strip of primer adhesive wide enough to cover the waterstop material (usually a minimum of 1 inch).
4. Allow primer adhesive to dry approximately 20 minutes (longer for cold temperatures).
5. Press waterstop firmly onto tacky primed surface.

Coverage

- Approximately 3,000 lft

Warranty Information

All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all

warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for the intended use, and user assumes all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacturer.



April 10, 2014

Earth Shield® Chemical Resistant Waterstop

551 Birch Street, Lake Elsinore, CA 92530

888-836-5778 • FAX 951-674-1315 • www.earthshield.com • davidp@earthshield.com